

## Digital Dry Bath Heat Blocks




- 정확한 digital 온도 설정시스템을 제공, 사용자 온도 보정기능 내장, 타이머 기능으로 히팅블럭 전원이 꺼지진 않지만, 설정한 시간 간격이 만료되었음을 사용자에게 알려줌.
- Aluminium block의 온도 전달 기능이 탁월.
- block 집게와 온도 절연 손잡이가 있음.

### Ordering Information


BSH1001	Single Dry Heat Block Bath (기본제공)
BSH1002	Dual Dry Heat Block Bath (기본제공)
BSH1004	Four Dry Heat Block Bath, (기본제공)

### Aluminium Block (Option)

BSW01	Block, solid, for slides or custom machining
BSW01-DR	Block, custom drilling for BSW01 (sold separately), up to 36 holes
BSW02	Block, 48 x 0.2ml tubes or 6 PCR strips
BSW05	Block, 24 x 0.5ml centrifuge tubes
BSWCMB	24 x 1.5ml/2.0ml & 14 x 0.5ml, 6 x PCR strips, 48 x 0.2ml or 1 PCR Plate (only two block)
BSW1500	Block, 24 x 1.5ml centrifuge tubes (conical)
BSW1520	Block, 24 x 1.5/2.0ml centrifuge tubes
BSW5MT	Block, 12 x 5ml snap cap centrifuge tubes
BSW15	Block, 12 x 15ml (block height: 8.2cm, Ø17)
BSW50	Block, 5 x 50ml (block height: 8.2cm)
BSW10	Block, 20 x 10mm (or 20 x 2.0ml)
BSW13	Block, 20 x 12/13mm (or 20 x 5/7ml blood tube)
BSW1516	Block, 12x15-16mm (or 12x10ml blood tube)
BSW24XL	Block, 24 x 1.5ml tubes or 32 x 0.2ml and 20 x 0.5ml tubes
BSWPCR2	Block, 1 x 96-well PCR plate (2&4 block models only)
BSWPCR1	Block, 1 x 96-well PCR plate (Single block model only)
BSWMT	Block, 1 x Micro Plate (2 & 4 block models only)



Included block lifter, for removal of hot blocks



Wide Variety of block options

### Technical Data

Temp. range :	Ambient +5 to 150°C 이내 ( four block max. 130°C )
Temp. accuracy :	+/- 0.2°C
Temp. 증가속도 :	0.1°C
Temp. 분포도 :	+/- 0.2°C
Calibration function :	User calibration available
Timer :	1 to 99h 59 min. / continuous
Alarm function :	Start, stop alarm function
Display :	Timer, temp. LED display
Dimension (wxdxh)cm :	20 x 23 x 8 cm (Single), 22 x 26 x 8 cm (Dual) 22 x 35.5 x 8 cm (four)
Block size (wxdxh)cm :	7.6 x 9.5 x 5cm
Electrical :	120V or 230V, 50/60Hz (1개용: 350W, 2개용: 600W, 4개용: 1000W)